

|  |                    |        |               |        |
|--|--------------------|--------|---------------|--------|
| <b>Nexans<br/>Ref. Code</b>                      |                    | - IT   | 10546324-IT   | - IT   |
|  |                    | - RO-B | 10546518-RO-B | - RO-B |
|  |                    | - RO-D | 10546519-RO-D | - RO-D |
|  |                    | - RO-M | 10549896-RO-M | - RO-M |
| <b>Formation</b>                                 |                    | 1x95   | 1x185         | 1x240  |
| <b>Nominal<br/>Conductor<br/>Diameter</b>        | [mm]               | 11,5   | 16,0          | 18,5   |
| <b>Minimum<br/>Insulation<br/>Thickness</b>      | [mm]               | 4,31   | 4,31          | 4,31   |
| <b>Nominal<br/>Insulation<br/>Diameter</b>       | [mm]               | 21,9   | 26,4          | 28,9   |
| <b>Aluminum<br/>tape<br/>Nominal<br/>Section</b> | [mm <sup>2</sup> ] | 25,5   | 30,0          | 33,0   |
| <b>Nominal<br/>Sheath<br/>Thickness</b>          | [mm]               | 2,75   | 2,75          | 3,00   |
| <b>Nominal<br/>Cable<br/>Diameter</b>            | [mm]               | 30,8   | 35,5          | 38,5   |
| <b>Indicative<br/>Cable<br/>Weight</b>           | [kg/km]            | 840    | 1.200         | 1.460  |